

DECLARATION OF PERFORMANCE

Compliant with the European Construction Products Regulation nº 305/2011

Nº ADH.007-240305



EN 12004-1:2017

1. PRODUCT

**CEMENTITIOUS
ADHESIVES**

**ADIMAR PLASTER
ADIMAR PROFESSIONAL
ADIMAR PORCELAIN
ADIMAR FLEXIBLE
ADIMAR FLEXIBLE GEL
ADIMAR TECNO FLEX
ADIMAR SUPERFLEX**

2. NAME AND ADDRESS OF THE MANUFACTURER

AYMAR S.A.U.

Carretera C-35 KM.58,
08470 SANT CELONI (BARCELONA)

3. INTENDED USE

- **Adhesives for ceramic tiles, EN 12004-1:2017**
Use for ceramic tiles for placement on walls, floors or ceilings.

4. EVALUATION AND VERIFICATION SYSTEM FOR THE CONSTANCY OF PERFORMANCE

System 3

5. NOTIFIED ORGANISM

Applus, nº 370
Initial Type Tests
System 3

Product Determination Type:

- ADIMAR PLASTER: 01/12/2010
- ADIMAR PROFESSIONAL: 01/10/2013
- ADIMAR POOL: 19/11/2013
- ADIMAR PORCELAIN: 01/10/2013
- ADIMAR FLEXIBLE: 10/05/2010
- ADIMAR FLEXIBLE GEL: 10/01/2023
- ADIMAR TECNO FLEX: 01/03/2015
- ADIMAR SUPERFLEX: 20/03/17

• Page 1 de 2 •



Plant and Office

Ctra. C-35, Km 58 · Ap. Correos nº1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es

6. DECLARED PERFORMANCES

CHARACTERISTICS ESSENTIAL		U.	PERFORMANCES						
			ADIMAR PLASTER	ADIMAR PROFESSIONAL	ADIMAR PORCELAIN	ADIMAR FLEXIBLE	ADIMAR FLEXIBLE GEL	ADIMAR TECNO FLEX	ADIMAR SUPERFLEX
			C1T	C1TE	C2TE	C2TE-S1	C2TE-S1	C2T-S1	C2TE-S2
			Normal-setting adhesive with reduced slip (not suitable for outdoor use)	Normal-setting adhesive with reduced slip	Improved adhesive with reduced slip and extended open time	Improved deformable adhesive with reduced slip and extended open time	Improved deformable adhesive with reduced slip and extended open time	Improved deformable cementitious adhesive with reduced slip	Highly deformable improved adhesive with reduced slip and extended open time
Kneading water	EN 12004-1 Section 6	%	24%	32%	32%	32%	32%	22%	30%
Initial Adhesion	EN 12004-2 Section 8.3	N/mm ²	≥ 0,5	≥ 0,5	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
Adhesion after immersion in water	EN 12004-2 Section 8.3	N/mm ²	≥ 0,5	≥ 0,5	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
Adhesion after heat aging	EN 12004-2 Section 8.3	N/mm ²	NDP	≥ 0,5	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
Adhesion after freeze-thaw cycles	EN 12004-2 Section 8.3	N/mm ²	NDP	≥ 0,5	≥ 1	≥ 1	≥ 1	≥ 1	≥ 1
Reaction to Fire	EN 12004-1 Section 4.4.2	Class	A1	A1	A1	A1	A1	A1	A1
Hazardous substances	EN 12004-2 Section 4.6		Complies section 4.6	Complies section 4.6	Complies section 4.6	Complies section 4.6	Complies section 4.6	Complies section 4.6	Complies section 4.6

The performance of the product identified in point 1 is in accordance with the performance declared in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed by and on behalf of the manufacturer:

Luis Jesús García-Muñoz Miras

Responsible for the Integrated Management System
Quality, Occupational Safety, Environment, Sustainable Mining

Sant Celoni, March 05, 2024