

DECLARATION OF PERFORMANCE

Compliant with European Construction Products Regulation No. 305/2011

Nº J004.01-240612



EN 13888-1:2022

1. PRODUCT

GROUTING MATERIAL FOR CERAMIC TILES

“ADIMAR UNIVERSAL JOINT”
 “ADIMAR TECHNICAL JOINT 0/16”
 “ADIPOXI”

2. NAME AND ADDRESS OF THE MANUFACTURER

AYMAR S.A.U.
 Carretera C-35 KM.58,
 08470 SANT CELONI (BARCELONA)

3. INTENDED USE

- **Jointing mortars for ceramic tiles and slabs. EN-13888:2009**
 Requirements, conformity assessment, classification and designation.

PRODUCT	TYPE	APPLICATION
ADIMAR UNIVERSAL JOINT	Cementitious grouting material CG2WA	Joint sealing mortar with high abrasion resistance and reduced water absorption
ADIMAR TECHNICAL JOINT 0/16	Cementitious grouting material CG2WA	Mortar for sealing joints from 0 to 16 mm., resistant to chemical aggressions, and very resistant to high temperatures. Ideal for SWIMMING POOLS.
ADIPOXI	Active resin grouting material RG	Acid-resistant joint sealing mortar, from 0 to 10 mm.

4. EVALUATION AND VERIFICATION SYSTEM FOR THE CONSTANCY OF PERFORMANCE

System 4.

Factory Production Control (CPF), Product Evaluation and Verification in accordance with:

- EN 13888:2022. Grouting materials for ceramic tiles. Requirements, conformity assessment, classification and designation.

5. DECLARED PERFORMANCE

CHARACTERISTICS ESSENTIAL		TECHNICAL SPECIFICATIONS	U.	PERFORMANCE		
				ADIMAR UNIVERSAL JOINT	ADIMAR TECHNICAL JOINT 0/16	ADIPOXI
				CG2WA	CG2WA	RG
Abrasion resistance	EN 13888-2	EN 13888-1:2022	mm ³	≤ 1000	≤ 1000	≤ 250
Flexural strength after dry storage	EN 13888-2		N/mm ²	≥ 2,5	≥ 2,5	≥ 30
Flexural strength after freeze-thaw cycles	EN 13888-2		N/mm ²	≥ 2,5	≥ 2,5	-
Compressive strength after dry storage	EN 13888-2		N/mm ²	≥ 15	≥ 15	≥ 45
Compressive strength after freeze-thaw cycles	EN 13888-2		N/mm ²	≥ 15	≥ 15	-
Retraction	EN 13888-2		mm/m	≤ 1,5	≤ 3	≤ 1,5
Water absorption after 30min	EN 13888-2		g	≤ 2	≤ 2	-
Water absorption after 240min	EN 13888-2		g	≤ 5	≤ 5	≤ 0,1

The performance of the product identified in point 1 is in accordance with the performance declared in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer referred to in point 2.

Luis Jesús García-Muñoz Miras

Responsible for the Integrated Management System
Quality, Occupational Safety, Environment, Sustainable Mining

Sant Celoni, June 12, 2024