

DECLARATION OF PERFORMANCE

Compliant with the European Construction Products Regulation nº 305/2011

Nº PR.003-220520



EN 13813:2002

1. PRODUCT

MORTARS FOR PAVEMENTS AND SCREEDS

SELF-LEVELING MORTAR L20
SELF-LEVELING MORTAR L20 PLUS
SELF-LEVELING MORTAR L50
ADILEVEL L15 C30
ADILEVEL THICK LAYER C35 F7
PAVIMAR GROWN-UPS
PAVIMAR GROWN-UPS – SWIMMING POOL SPECIAL

2. NAME AND ADDRESS OF THE MANUFACTURER

AYMAR S.A.U.

Carretera C-35 KM.58,
08470 SANT CELONI (BARCELONA)

3. INTENDED USE

- **Mortars for screeds and floor finishes, EN 13813:2002**
Mortars for screeds and floor finishes with a cement base (CT).

4. EVALUATION AND VERIFICATION SYSTEM FOR THE CONSTANCY OF PERFORMANCE

System 4



Plant and Office

Ctra. C-35, Km 58 · Ap. Correos nº1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es

5. DECLARED PERFORMANCE

CHARACTERISTICS ESSENTIAL		TECHNICAL SPECIFICATIONS	U.	PERFORMAN							
				CE							
				SELF-LEVELING L20	SELF-LEVELING L20 PLUS	SELF-LEVELING L50	ADILEVEL L15 C30	ADILEVEL THICK LAYER C35 F7	PAVIMAR GROWN-UPS	PAVIMAR GROWN-UPS SWIMMING POOL SPECIAL	
		EN 13813:2002		CT-C20-F5	CT-C20-F7-A22	CT-C25-F6	CT-C30-F4	CT-C35-F7	CT-C24-F6	CT-C25-F6	
Application Thickness	-		mm	<20	<20	<50	1--15	5-50	>10	>10	
Maximum size of aggregate used	EN 933-1		mm	1	1	3	1	4	3	3	
Emission of corrosive substances	---		Type of mortar	CT	CT	CT	CT	CT	CT	CT	
Compressive Strength	EN 13892-2		Category	>20 N/mm ² C20	>30 N/mm ² C30	>25 N/mm ² C25	>33 N/mm ² C30	< 35 N/mm ² C35	>24 N/mm ² C20	>25 N/mm ² C25	
Bending Strength	EN 13892-2		Category	F5	F7	F6	F4	F7	F6	F6	
Reaction to Fire	Commission decision 96/603/CE		Class	A1 _{fl}	A1 _{fl}	A1 _{fl}	A1 _{fl}	A1 _{fl}	A1 _{fl}	A1 _{fl}	
Wear resistance	EN 13892-3		Class	PND	A22	PND	PND	PND	PND	PND	
Water permeability	EN 1062-3		Class	PND	PND	PND	PND	PND	PND	PND	
Water vapour permeability	EN 12086		Class	PND	PND	PND	PND	PND	PND	PND	
Sound insulation	EN ISO 140-6		Class	PND	PND	PND	PND	PND	PND	PND	
Sound absorption	EN 12354-6		Class	PND	PND	PND	PND	PND	PND	PND	
Thermal resistance	EN 12524	Class	PND	PND	PND	PND	PND	PND	PND		
Chemical Resistance	EN 13529	Class	PND	PND	PND	PND	PND	PND	PND		


The performance of the product identified in point 1 is in accordance with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer referred to in point 2.

Luis Jesús García-Muñoz Miras

Responsible for the Integrated Management System
Quality, Occupational Safety, Environment, Sustainable Mining

Sant Celoni, May 20, 2022

20/05/22	L20 PLUS product is included, and normative test references are updated
----------	---



Plant and Office

Ctra. C-35, Km 58 · Ap. Correos nº1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es