

Fixmar primer GR

Printing and adhesion promoter based on acrylic polymers with low emission of volatile organic substances. Prepared to be used indoors and outdoors, with inert loads, giving it a textured surface.

Application

The **FIXMAR PRIMER GR** adhesion promoter is suitable to improve the adhesion of any type of plaster or plaster on concrete supports, brick, light block or plaster, also on non-absorbing substrates such as ceramic floors. On walls and floors, both exterior and interior. It is also suitable for application on non-absorbing substrates such as ceramic pavements for subsequent installation of ceramic or natural stone coatings.

On porous cement floors, anhydrite or sanding, the **FIXMAR PRIMER GR** acts as a fixer of dust remains, facilitating the correct adhesion and facilitating the correct adhesion of a self-leveling mortar. It also acts as pore filling.

Instructions for use

- **Support preparation:** The surfaces must be clean, dry, hardened, oil-free, fat and broken remains. Not is It is not necessary to wet the substrate before application.
- **Printing Application:** Shake before use and apply to the surface with a brush or roller. After timeout Self-leveling plaster, plaster or mortar can be applied.

Recommendations for use

- Apply to average temperatures between 50 and 350.
- Protect yourself from freezing.
- Do not use **FIXMAR FIRST GR** in the presence of water.
- Clean the tools with water after applying the printing.
- It is possible to apply a second layer of **FIXMAR FIRST GR** even if a long period has passed since of the first application.
- On porous or absorbing substrates, it can be diluted with water up to 20%.
- The waiting time before applying the self-leveling coating, plaster or mortar is 15 to 60 minutes depending on the support and atmospheric conditions.

Technical data

Product	Appearance	Creamy Liquid
	Color	Red
	Density	1,4±0,1 g/cm3
	pH	8
Application	Application temperature between 5° et 35°. 19-20%	
Consumption	0,2-0,3 Kg/m2	
Stockage	12 months under normal conditions within the original pre-closed packaging	
Presentation	FIXMAR PRIMER GR supplied in 5 kg packets.	

MADE IN SPAIN

To know the security precautions of use, storage and elimination of the product, consult the security data sheet available on the site www.aymarsa.es

NOTE: The information on this technical file is based on our experience and trials carried out in specialized laboratories. The characteristics of the product obtained will depend on the preparation and correct application in situ by the user. If these conditions are not met, the characteristics indicated above will not be obtained.



Plant and Offices

Ctra. C-35, Km 58 · Ap. correus n°1
08470 SANT CELONI (Barcelona)

Tel. (+34) 93 867 00 00

aymar@aymarsa.es
www.aymarsa.es




SGM-001/2009



ER-1277/2010



SST-006/2018



GA-2010/0955
Mina "XAUXA"

